



7 October 2025

Ref: 212218/10973

Muswellbrook Coal Company  
PO Box 123  
Muswellbrook NSW 2333

## **RE: SEPTEMBER 2025 NOISE MONITORING RESULTS – MUSWELLBROOK COAL**

This letter report presents the results of noise compliance monitoring, commencing at about 12:50 am on Thursday 4<sup>th</sup> of September, 2025, for the Muswellbrook Coal Company (MCC) operation at Muscle Creek Road, Muswellbrook. The monitoring was undertaken as per the requirements of D.A. 205/2002 and detailed in the Noise Management Plan (NMP) for the site. Monitoring was conducted by two members of Spectrum Acoustics personnel, hence the cross-over in monitoring period times for some monitoring locations.

### **Attended Noise Monitoring Program**

Noise monitoring was undertaken in accordance with the NMP as summarised below.

All attended monitoring and equipment maintenance and calibration is conducted in accordance with the Noise Policy for Industry (NPfI) and AS1055 – Acoustics, Description and Measurement of Environmental Noise.

Attended noise monitoring is undertaken monthly by an independent noise consultant. Each attended noise survey will be conducted during night periods only. If it is identified during the noise monitoring that the mining noise from the operation is exceeding the criteria, MCC will be notified and the operations will be modified as required. Monitoring at the location(s) where the noise levels are elevated will be undertaken again with a minimum break of 75 minutes between monitoring.

The noise criteria for MCC apply under all meteorological conditions except for the following:

- i. Wind speeds greater than 3m/s at 10m above ground level; or
- ii. Stability category F temperature inversion conditions and wind speeds greater than 2 m/s at 10m above ground level; or
- iii. Stability category G temperature inversion conditions.

To determine compliance with the Leq (15 min) operational noise criteria the modification factors detailed in Section 4 of the NPI must be applied, as appropriate, to the measured noise levels.

Due to the distance of the operation from each residence, the monitoring of LA1 (1minute) at the facade is not considered necessary and will be conducted at/or near the property boundary.

The attended noise monitoring locations are detailed in **Table 1** and shown in **Figure 1**.

| Table 1<br>Noise Monitoring Locations |                   |
|---------------------------------------|-------------------|
| Location                              | Description       |
| R13                                   | Sandy Creek Road  |
| R15                                   | Queen St          |
| R17                                   | Queen St          |
| R25                                   | Sandy Creek Road  |
| R32                                   | Muscle Creek Road |




Figure 1 – Noise Monitoring Locations

Noise criteria for all assessment locations shown in Figure 1 are detailed in **Appendix I** to this report.

## Monitoring Equipment

Attended noise monitoring was conducted with a Brüel & Kjær Type 2250 Precision Sound Analyser. This instrument has Type 1 characteristics as defined in AS1259-1990 “Sound Level Meters” and has current NATA calibration. Field calibration is carried out at the start and end of each monitoring period. Calibration certificates are attached as **Appendix II** to this report.

A-weighted noise levels were measured over the 15 minute monitoring period with data acquired of 1 second statistical intervals and the meter set to “fast” response. Each 1 second measurement is accompanied by a third-octave band spectrum from 20 - 20k Hz which is required for analysing NPI ‘modifying factors’.

Time based field notes allow for determination of the relative contributions to the overall noise level of all significant noise sources.

## Measurement Analysis

The MCC compliance noise criteria are based on a 15 minute Leq noise level. The 15 minute Leq noise level for each monitoring period is shown in the tables below. Where the noise from MCC was audible Bruel & Kjaer “*Evaluator*” analysis software was used to quantify the contribution of the operation and other significant noise sources to the overall level. Operational noise from MCC is shown in the table in bold type.

All noise levels shown are in dB(A) Leq (15 min) unless otherwise detailed.

## MCC Operations

Operational details for MCC for the monitoring period on the 4<sup>th</sup> of September 2025 (that is, after midnight on the 3<sup>rd</sup> of September) are detailed in **Appendix III**. At the time of the noise monitoring MCC had ceased mining operations and work was being undertaken to rehabilitate the site.

## Noise Compliance Assessment

The results of the noise measurements are shown in **Table 2**.

| Table 2                                                                   |         |               |                                   |                           |                                     |                                                  |                                                                |                                     |                                                                             |
|---------------------------------------------------------------------------|---------|---------------|-----------------------------------|---------------------------|-------------------------------------|--------------------------------------------------|----------------------------------------------------------------|-------------------------------------|-----------------------------------------------------------------------------|
| MCC Operational Noise Monitoring Results – 4 <sup>th</sup> September 2025 |         |               |                                   |                           |                                     |                                                  |                                                                |                                     |                                                                             |
| Location                                                                  | Time    | dB(A),<br>Leq | MCC<br>Contribution<br>dB(A), Leq | Criterion<br>dB(A)<br>Leq | dB(A),<br>L1<br>(1min) <sup>1</sup> | Criterion<br>dB(A),<br>L1<br>(1min) <sup>1</sup> | Stability<br>Class/<br>Wind<br>speed<br>(m/s)/dir <sup>o</sup> | Compliant<br>Met<br>Conditions<br>? | Identified Noise<br>Sources <sup>2</sup>                                    |
| R13<br>Sandy<br>Creek Rd.                                                 | 1:09am  | 38            | n/a                               | 41                        | n/a                                 | 45                                               | D/2.7/342                                                      | Yes                                 | Traffic (38), frogs (26),<br><b>MCC inaudible</b>                           |
| R15<br>Queen St.                                                          | 1:49am  | 34            | n/a                               | 37                        | n/a                                 | 45                                               | D/2.1/338                                                      | Yes                                 | Traffic (34), frogs (21),<br><b>MCC inaudible</b>                           |
| R17<br>Queen St.                                                          | 2:13am  | 40            | n/a                               | 35                        | n/a                                 | 45                                               | D/1.8/333                                                      | Yes                                 | Train (38), traffic (34),<br>dogs (31), frogs (20),<br><b>MCC inaudible</b> |
| R25<br>Sandy<br>Creek Rd.                                                 | 12:49am | 35            | n/a                               | 42                        | n/a                                 | 45                                               | D/2.4/007                                                      | Yes                                 | Frogs (34), traffic (25),<br><b>MCC inaudible</b>                           |
| R32<br>Muscle<br>Creek Rd.                                                | 1:40am  | 68            | n/a                               | 35                        | n/a                                 | 45                                               | D/2.1/338                                                      | Yes                                 | Trains (68), frogs (24),<br><b>MCC inaudible</b>                            |

1. L1 (1 min) from MCC operational noise only

2. See text regarding MCC noise sources

The results in Table 2 show that, under the operational and meteorological conditions at the time, operational noise from MCC was inaudible at all monitoring locations throughout the survey.

Table 2 also shows that the noise was not consistent enough to be measurable at any monitoring location.

The data from the site operated weather station showed that meteorological conditions were compliant with the conditions in the NMP for the noise monitoring surveys conducted at all monitoring locations.

As indicated above, noise from MCC was not measurable or quantifiable at any monitoring location.

Data from those times where MCC operations were audible during the monitoring survey were analysed using the “*Evaluator*” software. This analysis showed the noise did not contain any tonal or impulsive components as per definitions in the NPI.

The methodology for analysing the low frequency noise modifying factor correction in the NPI is shown in extract below.

|                     |                                                                                                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                        |                                                                                                                                                                                                                                                                                                                                   |
|---------------------|------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Low-frequency noise | Measurement of source contribution C-weighted and A-weighted level and one-third octave measurements in the range 10– 160 Hz | Measure/assess source contribution C- and A-weighted Leq,T levels over same time period. Correction to be applied where the C minus A level is 15 dB or more and: <ul style="list-style-type: none"> <li>where any of the one-third octave noise levels in Table C2 are exceeded by up to and including 5 dB and cannot be mitigated, a 2-dB(A) positive adjustment to measured/predicted A-weighted levels applies for the evening/night period</li> <li>where any of the one-third octave noise levels in Table C2 are exceeded by more than 5 dB and cannot be mitigated, a 5-dB(A) positive adjustment to measured/predicted A-weighted levels applies for the evening/night period and a 2-dB(A) positive adjustment applies for the daytime period.</li> </ul> | 2 or 5 dB <sup>2</sup> | A difference of 15 dB or more between C- and A-weighted measurements identifies the potential for an unbalance spectrum and potential increased annoyance. The values in Table C2 are derived from Moorhouse (2011) for DEFRA fluctuating low-frequency noise criteria with corrections to reflect external assessment locations. |
|---------------------|------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**Table C2 : One-third octave low-frequency noise thresholds.**

| Hz/dB(Z)       | One-third octave dB(Z) Leq (15 min) threshold level |      |    |    |    |      |    |    |    |    |     |     |     |
|----------------|-----------------------------------------------------|------|----|----|----|------|----|----|----|----|-----|-----|-----|
| Frequency (Hz) | 10                                                  | 12.5 | 16 | 20 | 25 | 31.5 | 40 | 50 | 63 | 80 | 100 | 125 | 160 |
| dB(Z)          | 92                                                  | 89   | 86 | 77 | 69 | 61   | 54 | 50 | 50 | 48 | 48  | 46  | 44  |

The correction applies to the site noise component only. There are many sources of low frequency noise in the acoustic environment of each receiver area (including noise from road and rail traffic). In many cases the C minus A level is greater than 15 due to these other noise sources. In most instances the screening criteria will be the one third octave analysis. The NPI quantitative assessment of noise from MCC can only be conducted where the noise was clearly definable, which is at a level typically greater than 30 dB(A) or when there are no other significant sources. Due to this, quantitative assessment of low frequency noise was not possible.

In addition to the operational noise, the noise from MCC must not exceed **45 or 47 dB(A) L1 (1 min)** between the hours of 10 pm and 7 am (see Appendix I for details of noise criteria at various receiver locations). This is to minimise the potential for sleep disturbance as a result of individual loud noises from the operation.

The compliance measurement locations are different for each of the operational and sleep disturbance noise. That is, the sleep disturbance criterion is typically applicable at 1m from the facade of a bedroom window.

To avoid undue disturbance to residents the L1 (1 min) noise level from the operational measurements are used to show general compliance with the sleep disturbance criterion. That is, as the distance between the noise source and the operational noise monitoring location is significantly greater than the distance between the operational noise monitoring location and the sleep disturbance monitoring location (i.e. 1m from the facade of the house) there will be little variation in L1 (1 min) levels between the two monitoring locations.

It must be noted, however, that the sleep disturbance criterion is applicable at the outside of a bedroom window. As the internal layout of each residence is not known, to consider a worst case, the bedroom windows were assumed to be facing towards the site.

As shown in Table 2, during the night time measurement circuit the L1 (1 min) noise from MCC did not exceed 45 dB(A) at any monitoring location.

We trust this report fulfils your requirements at this time, however, should you require additional information or assistance please contact the undersigned on (02) 4954 2276.

Yours faithfully,

**SPECTRUM ACOUSTICS PTY LIMITED**

Author:



**Neil Pennington**  
Acoustical Consultant

## Appendix I

Noise criteria from Development Consent DA205/2002 (Locations as per Figure 1).

| Location                                                                             | Day                          | Evening                      | Night                        |                            |
|--------------------------------------------------------------------------------------|------------------------------|------------------------------|------------------------------|----------------------------|
|                                                                                      | L <sub>Aeq</sub> (15 minute) | L <sub>Aeq</sub> (15 minute) | L <sub>Aeq</sub> (15 minute) | L <sub>A1</sub> (1 minute) |
| R1, R2, R3, R4, R17, R26, R27, R28, R29, R30, R31, R32, R33, R34, R35, R37, R38, R39 | 35                           | 35                           | 35                           | 45                         |
| R5                                                                                   | 36                           | 36                           | 36                           | 45                         |
| R7                                                                                   | 38                           | 38                           | 38                           | 45                         |
| R11                                                                                  | 39                           | 39                           | 39                           | 45                         |
| R12                                                                                  | 39                           | 39                           | 39                           | 45                         |
| R13                                                                                  | 41                           | 41                           | 41                           | 45                         |
| R14                                                                                  | 38                           | 38                           | 38                           | 45                         |
| R15                                                                                  | 37                           | 37                           | 37                           | 45                         |
| R16                                                                                  | 36                           | 36                           | 36                           | 45                         |
| R17                                                                                  | 35                           | 35                           | 35                           | 45                         |
| R18                                                                                  | 45                           | 38                           | 37                           | 47                         |
| R20                                                                                  | 45                           | 38                           | 37                           | 47                         |
| R21                                                                                  | 37                           | 37                           | 37                           | 45                         |
| R22                                                                                  | 39                           | 39                           | 39                           | 45                         |
| R23                                                                                  | 39                           | 39                           | 39                           | 45                         |
| R24                                                                                  | 40                           | 40                           | 40                           | 45                         |
| R25                                                                                  | 42                           | 42                           | 42                           | 45                         |
| R36                                                                                  | 38                           | 38                           | 38                           | 45                         |
| R40                                                                                  | 42                           | 42                           | 42                           | 45                         |
| R41                                                                                  | 42                           | 42                           | 42                           | 45                         |
| R42                                                                                  | 40                           | 40                           | 40                           | 45                         |

Note: All levels are in dB(A)

Note: Following further consultation with the community it has been identified that R11 is a stable complex, not a residence, so the criteria listed in the table above do not apply.

## Appendix II

### Calibration Certificates



**NVMS**

Sydney Calibration Laboratory  
Unit 21, 1 Talavera Road, Macquarie Park NSW 2113, Australia  
Accredited for compliance with ISO/IEC 17025 - Calibration. Laboratory No. 1301



**NATA**

WORLD RECOGNISED  
ACCREDITATION

**CERTIFICATE OF CALIBRATION**

Certificate No: CAU2401038

Page 1 of 11

---

**CALIBRATION OF:**

|                      |                      |                   |             |
|----------------------|----------------------|-------------------|-------------|
| Sound Level Meter:   | Brüel & Kjær         | 2250              | No: 3030460 |
| Microphone:          | Brüel & Kjær         | 4189              | No: 3318407 |
| Preamplifier:        | Brüel & Kjær         | ZC-0032           | No: 31079   |
| Supplied Calibrator: | Brüel & Kjær         | 4231              | No: 2466354 |
| Software version:    | BZ7223 Version 4.7.6 | Pattern Approval: | -           |
| Instruction manual:  | BE1712-22            | Identification:   | N/A         |

---

**CUSTOMER:**

Spectrum Acoustics Pty Ltd  
8 Panylan St  
Cardiff NSW 2285

---

**CALIBRATION CONDITIONS:**

Preconditioning: 4 hours at 23 °C  
Environment conditions: *see actual values in Environmental conditions sections*

---

**SPECIFICATIONS:**

The Sound Level Meter has been calibrated in accordance with the requirements as specified in IEC61672-1:2013 class 1. Procedures from IEC 61672-3:2013 were used to perform the periodic tests. The measurements included in this document are traceable to Australian / International standards through accredited calibration of all relevant reference equipment.

---

**PROCEDURE:**

The measurements have been performed with the assistance of Brüel & Kjær Sound Level Meter Calibration System B&K 3630 with application software type 7763 (version 8.6 - DB: 8.60) and test procedure 2250-4189.

---

**RESULTS:**

|   |                                       |                                        |
|---|---------------------------------------|----------------------------------------|
|   | Initial calibration                   | Calibration prior to repair/adjustment |
| X | Calibration without repair/adjustment | Calibration after repair/adjustment    |

The reported expanded uncertainty is based on the standard uncertainty multiplied by a coverage factor  $k = 2$  providing a level of confidence of approximately 95 %. The uncertainty evaluation has been carried out in accordance with EA-4/02 from elements originating from the standards, calibration method, effect of environmental conditions and any short time contribution from the device under calibration.


---

Date of Calibration: 04/11/2024

Certificate issued: 06/11/2024



Barath Chandar Rajendran  
Calibration Technician



Sajeeb Tharayil  
Approved signatory

Reproduction of the complete certificate is allowed. Parts of the certificate may only be reproduced after written permission.



Sydney Calibration Laboratory  
Unit 21, 1 Talavera Road, Macquarie Park NSW 2113, Australia  
Accredited for compliance with ISO/IEC 17025 - Calibration. Laboratory No. 1301



**NATA**  
WORLD RECOGNISED  
ACCREDITATION

CERTIFICATE OF CALIBRATION

Certificate No: CAU2401037

Page 1 of 5

CALIBRATION OF:

Acoustic Calibrator:Bruel & Kjaer 4231No: 2466354

Identification:N/A

CLIENT:

Spectrum Acoustics Pty Ltd

8 Panylan St

Cardiff NSW 2285

CALIBRATION CONDITIONS:

Preconditioning:12 hours at 23 °C

Environment conditions

Air temperature:23.6 °C ± 3°C

Air pressure:100.6 kPa ± 3 kPa

Relative Humidity:53.0 %RH ± 20 %RH

SPECIFICATIONS:

The acoustic calibrator has been calibrated in accordance with the requirements as specified in IEC 60942:2003 class 1. The measurements included in this document are traceable to Australian / International standards through accredited calibration of all relevant reference equipment.

PROCEDURE:

The measurements have been performed with the assistance of Brüel & Kjær Sound Level Meter Calibration System B&K 3630 with application software type 7794 (version 8.6 - DB: 8.60) and test procedure P\_4231\_4192\_M01.

RESULTS:

|   |                                       |  |                                        |
|---|---------------------------------------|--|----------------------------------------|
|   | Initial calibration                   |  | Calibration prior to repair/adjustment |
| X | Calibration without repair/adjustment |  | Calibration after repair/adjustment    |

The reported expanded uncertainty is based on the standard uncertainty multiplied by a coverage factor  $k = 2$  providing a level of confidence of approximately 95 %. The uncertainty evaluation has been carried out in accordance with EA-4/02 from elements originating from the standards, calibration method, effect of environmental conditions and any short time contribution from the device under calibration.

Date of Calibration: 04/11/2024

Certificate issued: 06/11/2024



Barath Chandar Rajendran  
Calibration Technician



Sajeeb Tharayil  
Approved signatory

Reproduction of the complete certificate is allowed. Parts of the certificate may only be reproduced after written permission.

## Appendix III

### Operational Details – 3 September 2025 (4:45pm to 2:45am)

#### D10 Dozer & Loader

- 1 x D10 operated from (5:30 – 6:45pm) and 1 x loader operated throughout the shift

#### Civil Equipment

2 x 36t excavators, 2 x D6 Dozers and 1 x Moxy truck moving between Zones 2 – 6 throughout the night depending on tasks

